

Technical Data Sheet

Product code: **AMC-L400**
Description: **Unidirectional Multiaxial Cloth**
Fibre type: E-Glass 300 tex
E-Glass 1500 tex
E-Glass 2400 tex

CONSTRUCTION	LAYER WEIGHT (g/m ²)	TOLERANCE (± %)	MATERIAL
0°	413	5	E-Glass 1500 tex
90°	54	5	E-Glass 300 tex
Mat	50		E-Glass 2400 tex
Knitting Yarn	12	5	Polyester 110 d'tex
Total Weight	530 g/m ²	5	
Stitch gauge	7 per inch (2.75/cm)	Stitch style	Tricot Stitch
Knitting yarn	Polyester 110d'tex	Stitch length	3.6 cpcm

Standard Roll Width: 1270mm (±5%)
Standard Roll Weight: 35 kg
Standard Roll Area: 69.9 m²
Standard Roll Length: 55 m
Packaging: Wrapped in PVC and placed within a cardboard carton. Positioned securely on to a pallet, strapped and covered.
Traceability: All fabrics are identified with a unique style number and all rolls produced have unique batch numbers.
Labelling: All rolls of material have a label placed within the core, on the roll and on the carton for clear identification.
Type Approvals: Lloyds Register

Importers and Distributors:



3 Civil Place, Albany
Ph: 09 476 1377

www.fibreglass-supplies.com