

Technical Data Sheet

Product code: **AMC-DBT920**
Description: **Weft Triaxial Cloth**
Fibre type: E-Glass 600 tex
E-Glass 1200 tex

CONSTRUCTION	LAYER WEIGHT (g/m ²)	TOLERANCE (± %)	MATERIAL
+45°	200	5	E-Glass 300 tex
90°	520	5	E-Glass 1200 tex
-45°	200	5	E-Glass 300 tex
Colour Tracer			Red/Blue
Stitching	8	5	Polyester 83 d'tex
Total Weight	928 g/m ²	5	
Stitch gauge	6 per inch (2.36/cm)	Stitch style	Pillar Stitch
Knitting yarn	Polyester 83d'tex	Stitch length	4.72 cpcm

Fabric Width: 1270 mm (±5%)
Nominal Roll Weight: 35 kgs
Standard Roll Area: 37.5 m²
Standard Roll Length: 29.5 m
Packaging: Wrapped in PVC and placed within a cardboard carton. Positioned securely on to a pallet, strapped and covered.
Traceability: All fabrics are identified with a unique style number and all rolls produced have unique batch numbers.
Labelling: All rolls of material have a label placed within the core, on the roll and on the carton for clear identification.
Approvals: Lloyds Register.

Importers and
Distributors:



3 Civil Place, Albany
Ph: 09 476 1377

www.fibreglass-supplies.com