

# Technical Data Sheet

Product code: **AMC-DBM400/225**  
 Description: **Double Bias Multiaxial Cloth – CSM Backed**  
 Fibre type: ECR-Glass 275 tex  
               E-Glass 2400 tex  
               E-Glass 68 tex

CONSTRUCTION	LAYER WEIGHT (g/m <sup>2</sup> )	TOLERANCE (± %)	MATERIAL
<b>+45°</b>	199	5	ECR-Glass 275 tex
<b>0°</b>	2.7	5	E-Glass 68 tex
<b>90°</b>	2.7	5	E-Glass 68 tex
<b>-45°</b>	199	5	ECR-Glass 275 tex
<b>Mat</b>	225	5	E-Glass 2400 tex
<b>Knitting Yarn</b>	8	5	Polyester 83 d'tex
<b>Total Weight</b>	630 g/m <sup>2</sup>	5	
<b>Stitch gauge</b>	6 per inch (2.36/cm)	<b>Stitch style</b>	Pillar Stitch
<b>Knitting yarn</b>	Polyester 83d'tex	<b>Stitch length</b>	4.72 cpcm

Standard Roll Width: 1270mm (±5%)

Standard Roll Weight: 32 kg

Standard Roll Area: 50.8m<sup>2</sup>

Standard Roll Length: 40 m

Packaging: Wrapped in PVC and placed within a cardboard carton. Positioned securely on to a pallet, strapped and covered.

Traceability: All fabrics are identified with a unique style number and all rolls produced have unique batch numbers.

Labelling: All rolls of material have a label placed within the core, on the roll and on the carton for clear identification.

Approvals: Lloyds Register

Importers and  
Distributors:



3 Civil Place, Albany  
Ph: 09 476 1377

[www.fibreglass-supplies.com](http://www.fibreglass-supplies.com)