

Technical Data Sheet

Product code: **AMC-DBM600/225**
 Description: **Double Bias Multiaxial Cloth – CSM Backed**
 Fibre type: ECR-Glass 600 tex
 E-Glass 2400 tex

CONSTRUCTION	LAYER WEIGHT (g/m ²)	TOLERANCE (± %)	MATERIAL
+45°	301	5	ECR-Glass 600 tex
0°	2.7	5	E-Glass 68 tex
90°	2.7	5	E-Glass 68 tex
-45°	301	5	ECR-Glass 600 tex
Mat	225	5	E-Glass 2400 tex
Knitting Yarn	8	5	Polyester 83 d'tex
Total Weight	835 g/m ²	5	
Stitch gauge	6 per inch (2.36/cm)	Stitch style	Pillar Stitch
Knitting yarn	Polyester 83d'tex	Stitch length	4.72 cpcm

Standard Roll Width: 1270 mm (±5%)

Standard Roll Weight: 32 kg

Standard Roll Area: 38.7 m²

Standard Roll Length: 30.5 m

Packaging: Wrapped in PVC and placed within a cardboard carton. Positioned securely on to a pallet, strapped and covered.

Traceability: All fabrics are identified with a unique style number and all rolls produced have unique batch numbers.

Labelling: All rolls of material have a label placed within the core, on the roll and on the carton for clear identification.

Approvals: Lloyds Register

Importers and
Distributors:



3 Civil Place, Albany
Ph: 09 476 1377

www.fibreglass-supplies.com